

MATERIAL SAFETY DATA SHEET ZINCBRITE (Aerosol)

1. IDENTIFICATION :	
COMPANY :	ITW INDIA LIMITED
ADDRESS :	PLOT NO 34 – 37, PHASE -2,
	APIIC, PASHAMMYLARAM,
	MEDAK – 502 307 (35 KM FROM HYDERABAD)
	INDIA.
EMERGENCY CELL No:	91-9000031515
TELEPHONE:	91 - 8455 - 224700
FAX:	91 - 8455 - 224705
PRODUCT USE:	Anti corrosive coating
PACKAGES :	Aerosol.
NFPA RATING:	Health 1, Flammability (Aerosol 4), Reactivity 0.
REVISION DATE:	Mar'2010

2. HAZARDOUS INGREDIENTS:							
	Wt/wt%	CAS# T	LV	LD 50	L	C 50	R-Phrases
Zinc Dust	20-30	7440-66-6	NE	NE		NE	
Xylene	10-30	1330-20-7	434 mg/m³	6,700 ppm.	4.3	g/kg	R 10,20,28,30
1-nitropropane:	< 0. 5 %	108-03-2	Not available				R 10, 20/21/22
Nitro ethane :	< 0.1 %	79-24-3	Not avail				R 10,20/22
Iso butane :	30-50%	75-28-5	not avail	1000ppm	not avail	not avail	R11

3. HAZARDS IDENTIFICATION:

Important Hazards-Fire:	Highly Flammable.
	Gas/Vapor explosive with air with in explosion limits.
	The vapors are heavier than air ,spreads along the ground.
	In use ,may form flammable /explosive vapor -air mixture.
	Pressurized container.
	Aerosol may explode under the affect of heat.
Environmental Hazards:	May cause long term adverse effects in aquatic environment.
POTENTIAL HEALTH EFFECTS	S & SIGNS AND SYMPTONS OF EXPOSURE:
Skin Contact:	Can irritate. Prolonged contact can cause redness, swelling and cracking of
Eyes:	May irritating, but does not damage eye tissue.
Inhalation:	Vapors may cause dizziness and nausea.
Ingestion:	Not significant in small (mouthful) amounts.
	Environmental Hazards: POTENTIAL HEALTH EFFECTS Skin Contact: Eyes: Inhalation:

4. FIRST AID :

Skin Contact:	Remove contaminated clothing. Wash exposed areas with soap and
water.	
Eyes:	Rinse carefully under upper and lower eyelids using plenty of
water for at least 10 min.	
Inhalation:	Remove to fresh air if dizzy or nauseated. In case of loss of
	consciousness, give artificial respiration.
Ingestion:	Do not induce vomiting. Accidental ingestion of a single
	mouthful is not expected to cause significant harm. Rinse
	mouth with water.
NOTE:	In all severe cases, contact physician immediately.

5. FIRE HAZARD :

Conditions of flammability:	Bulk & Aerosol: Ignition will occur if used near flames, arcs
or any other ignition source.	
Flash point:	>34 deg F(Pensky Marten closed cup)
Flammable limits in air:	2% to 15%
Extinguishing media:	Carbon Dioxide, foam, water, dry chemicals
Special fire fighting procedures:	Keep containers cool with water spray.
Hazardous combustion products:	Smoke, soot, oxides of carbon
Unusual fire hazards:	Aerosol cans may burst at temperatures over 50 0 C and add
	to existing fire.
Special Protective equipment	Full protective clothing and self containing breathing
	apparatus.
for fighters:	

6. ACCIDENTAL RELEASE MEASURES:

Personal Precautions:	Personal Protection Equipment must be worn. See Section 8.
Methods for Cleaning up:	
on Soil:	
	Prevent product from entering drains \surface water\ground
water.	
	Remove sources of ignition.
	Mop up or sweep up with absorbent (For disposal, see

Section 13)

Handling:	Ensure good ventilation.
U U	Do not spray on a naked flame or any incandescent material.
	Do not pressurize ,cut ,heat or weld containers(empty produc containers may contain product residue)
	Do not handle, store or open near an open flame, sources of
hea	t or sources of ignition.
	Do not smoke.
Storage:	Avoid proximity or contact with hot surfaces, flames or
ks.	
	Store in dry, cool, well ventilated area.
	Keep container tightly closed.
	Protect from sunlight and do not expose to temperature
eding 50 [°] C.	
-	Keep away from heat.
	Keep away from all sources of ignition.
	Avoid breathing vapors.
	Avoid eye contact.
	Avoid repeated or prolonged skin contact.
	Avoid breathing spray mist.
Packaging:	
-General	Do not pierce or burn, even after use.
8. EXPOSURE CONTROL	S/PERSONAL PROTECTION :
Recommended Engineering:	When using, do not eat ,drink or smoke.
Controls	None, unless sprayed. Use where ventilation will carry spray
away from occupied areas.	

Personal protection:	
Respiratory protection :	Ensure good ventilation.
	High vapor concentration: gas mask, filter A.
	In case of insufficient ventilation wear suitable respiration equipment.
	Respirator with filter if sprayed in enclosed unventilated
space.	
Skin and hand protection:	Handle according to good industrial hygiene and safety
procedures.	Appropriate protective
clothing and gloves.	
	Wear nitrile rubber gloves if hand exposure is unavoidable.

Eye protection : Wear safety glasses to protect eyes.

9. PHYSICAL PROPERTIES :

Physical and chemical properties of active product without propellant.

These are indicative values only. Please refer to product specification sheet.

Appearance: Odor: pH: Initial boiling point: Flash point; Vapor pressure: Oxidizing properties: Pour point: Water solubility: Density\Sp gravity: Grey Solvent Not Applicable >90 $^{\circ}$ C >34 $^{\circ}$ F 19Kpa Not applicable Not applicable. Not miscible 800 kg/m³

10.	STABILITY AND REACTIVITY:
10.	

Stability: Conditions to avoid:

. Strong Incompatibility: None Ku Hazardous decomposition products: Carbon di oxide, Reactivity: None Ku

Stable in normal conditions of use. Temperatures above 50^{°0} Avoid proximity or contact with flames or sparks Strong oxidizing agents, strong acids None Known. Carbon di oxide, Carbon monoxide ,Aldehydes and Ketones None Known.

11. TOXICOLOGICAL INFORMATION

(Based on test with similar products). (Refers to active component) No toxicological information available. Oral LD (50 rat): Dermal LD(50 Rabbit): Inhalation LC (50 Rat/4h): Skin contact: Eye Contact: tissue. Inhalation:

Ingestion: Skin Sensitization test: Mutagen city and Carcinogenicity: >2000mg\kg No information available No information available. Slightly irritant. Will cause eye discomfort, but will not injure eye

Avoid breathing vapors or mists. Irritating to respiratory system. Minimal toxicity. Data not available. No information available.

Mobility :	Should be kept out of sewage and drainage systems
podies of	
	water
<i>Degradability:</i> adable.	The product is expected to be partially or slowly
<i>Ecotoxicity and bioaccumulation</i>	<i>on:</i> Expected to be toxic to aquatic organisms.
13 DISPOSAL :	
Disposal of product:	This product is not suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. Dispose of in a safe manner ,in accordance with loc
	regulations
Disposal of packing:	Dispose of in a safe manner ,in accordance with loc regulations. Empty aerosol cans before disposal. Non hazardous waste as per classification in The
	Hazardous Wastes (Management and Handling) Rule
DCDA	1989, of CPB, India
RCRA: U.S EPA	hazardous waste Waste number: D001
	Waste Humber, Door
14 TRANSPORTATION :	
Labels Required :Flamma HAZCHEM 2Y	ble gas
Land Transport UNDG:	
Dangerous Goods Class: 2.	
UN Number: 1950	Packing Group: None
Shipping Name: AEROSO	LS
Air Transport IATA:	
ICAO/IATA Class:	2.1 ICAO/IATA Sub risk: None
UN/ID Number: ERG Code:	1950 Packing Group: 203 10L
Shipping Name: Aerosols	
	, indiminuolo
Maritime Transport IM	
Maritime Transport IM IMDG Class: 2	2 IMDG Sub risk: SP63
Maritime Transport IM IMDG Class: 2 UN Number: 1	2 IMDG Sub risk: SP63 1950 Packing Group: None
Maritime Transport IM IMDG Class: 2 UN Number: 1	2 IMDG Sub risk: SP63 950 Packing Group: None F-D, S-U Marine Pollutant: Not Determined
Maritime Transport IMIIMDG Class:2UN Number:1EMS Number:FShipping Name:AEROSO	2 IMDG Sub risk: SP63 950 Packing Group: None F-D, S-U Marine Pollutant: Not Determined LS
Maritime Transport IMIIMDG Class:2UN Number:1EMS Number:H	2 IMDG Sub risk: SP63 950 Packing Group: None F-D, S-U Marine Pollutant: Not Determined

15. **REGULATORY INFORMATION :**

Γ

	15. REGULATORI INFORM		
	TSCA: All ingredients are listed in TSCA inventory		
	CERCLA: Reportable quantity for Acetone=5000lbs		
	SARA TITLE III, Section 313: Ac	etone	
	California Proposition 65: Contain	S	
	EEC Labeling information:		
	Hazard Symbols:	Highly Flammable	
		Irritant: Xi	
		Dangerous for Environment: N	
		0	
	Risk phrases:	R11: Highly Flammable.	
		R38: Irritating to Skin.	
		R 51\53: Toxic to aquatic organisms, may cause long term	
	adverse effects in the aqu		
		Environment.	
		R 67: Vapors may cause drowsiness and dizziness.	
	Safety phrases:	Pressurized container .Protect from sunlight and do not	
	× 1	expose to temperatures exceeding 50 0 C. Do not pierces or	
		burn after use .Do not spray on naked flame or any	
		incandescent material l. Keep away from sources of ignition-	
		No smoking. Keep out of reach of children. With out adequate	
		ventilation formation of explosive mixtures may be possible.	
		r in it is in the second se	
		S23.2: Do not breathe vapor	
		S23.4: Do not breathe spray.	
		S46: If swallowed seek medical advice immediately and show	
		this container or Label.	
_		S 51: Use only in ventilated areas.	
	.16. OTHER INFORMATION:		
	Sources of Key data used:	Raw material supplier's data sheets were used as key data	
sources	in the preparation		
		Of this safety data sheet.	
	Risk phrases used in Sec.3:		
		R 11: Highly Flammable	
		R 20:Harmful by inhalation	
		R22: Harmful if swallowed	
		R36/38: Irritating to Eyes and skin.	
		R51/53: Toxic to aquatic organizations, may cause long term	
		adverse effects in the aquatic environment.	
		R 65: Harmful, may cause lung damage if swallowed.	
		R66 : Repeated exposure may cause skin dryness or	
		cracking.	
		R67 Vapors may cause drowsiness and dizziness.	
	Revision Statement:	New Product	
	Supersedes:	Nil	
	-		

The contents and format of this MSDS are in accordance with EC Commission Directive.